SMK

Single-Rail KVM Drawer Rackmount



The Challenge

The integration of data, video and voice communication in computers and the subsequent technological advances have spawn many sophisticated CTI applications that have become accessible and affordable to the small and mid-sized business. The increasing CTI applications coupled with the growing demand for corresponding hardware and systems have created a dilemma: How does one pack the growing number of equipment into existing space?

Features

- Single rail, multi-LCD monitor keyboard switch drawer
- VGA inputs for simultaneous display
- Keyboard/touchpad selector butons for each PC
- 105-key multi-language keyboard with touchpad
- 100W, 100~240VAC auto-switch power supply

The Solution

Acme's 1U slim industrial monitor keyboard, the SMK, is the solution for compacting more computing power into limited space. This revolutionary monitor keyboard combines a spectacular display coupled with a keyboard with built-in pointing device in a compact unit that measures only 1U in height. Occupying a fraction of the space of traditional monitor and keyboard units, the installation of the SMK leaves ample space for other critical components. With built-in analog-to-digital conversion board, the SMK can be connected to any standard VGA graphics card for immediate on-screen display. The monitor keyboard unit has a built-in slide rail and mounts easily onto any 19" rackmount cabinet.

SMK



D-Sub 15 pin single-port, 8-port, or 16-port with console



Self-locking rails



105 keys + 2-button touchpad

Technical Specifications

Product Version	SMK 920	SMK 980	SMK 990
Ports	D-Sub 15 pin single-port KVM	8x D-Sub 15 pins KVM ports	16x D-Sub 15 pins KVM ports
Diagonal	17" or 19", 5:4 Display		
LCD Resolution	1280 x 1024		
Brightness	300 nits		
Contrast Ratio	500:1		
Viewing Angle	170° (H) x 160° (V)		
Color	16.2M Colors		
Backlight MTBF	50,000 Hours under 25±5°C		
Power	60W, 100-240VAC, 50/60Hz		
Keyboard/Mouse	105-key cherry switch keyboard with touchpad		
Dimensions/Weight	1.73" x 17.42" x 21.65" (H x W x D) / 40 lbs		
Environmental Specifications			
Operating Temperature	0-50°C (32-122°F)		
Approval	CE, FCC, UL, CCC, RoHS		
	Get Quote	Get Quote	Get Quote

US - ACME Headquarters

ACME Portable Machines, Inc.
1330 Mountain View Circle, Azusa, CA
Tel: (626) 610-1888
Fax: (626) 610-1881
Email: sales@acmeportable.com

http://www.acmeportable.com

Germany - ACME Branch

ACME Portable Computer GmbH
Benzstrasse 15, 76185 Karlsruhe
Tel: +49 (0) 721-570 453-0
Fax: +49 (0) 721-570 453-29
Email: info@acmeportable.de

http://www.acmeportable.de

Taiwan - ACME Branch

ACME Portable Corp.
5F, No. 25, Wu Chuan 3rd Road,
Wu-Ku Ind. Park, New Taipei City, Taiwan
Tel: 888-2-2298-3636
Email: info@acmeportable.com.tw

http://www.acmeportable.com.tw