TRIDENT

Triple Screen Rackmount



TRIDENT

The Challenge

The integration of data, video and voice communication in computers and the subsequent technological advances have spawn many sophisticated CTI applications that have become accessible and affordable to the small and mid-sized business. The increasing CTI applications coupled with the growing demand for corresponding hardware and systems have created a dilemma: How does one pack the growing number of equipment into existing space?

The Solution

Acme's 1U slim industrial monitor keyboard, the SMK, is the solution for compacting more computing power into limited space. This revolutionary monitor keyboard combines a spectacular display coupled with a keyboard with built-in pointing device in a compact unit that measures only 1U in height. Occupying a fraction of the space of traditional monitor and keyboard units, the installation of the SMK leaves ample space for other critical components. With built-in analog-to-digital conversion board, the SMK can be connected to any standard VGA graphics card for immediate on-screen display. The monitor keyboard unit has a built-in slide rail and mounts easily onto any 19" rackmount cabinet.



D-Sub 15 pin input ports
for each PC



105 keys + 2-button touch pad
+ selector buttons



Independent OSD adjustment
for each monitor

Features

- Single rail, multi-LCD monitor keyboard switch drawer
- VGA inputs for simultaneous display
- Keyboard/touchpad selector butons for each PC
- 105-key multi-language keyboard with touchpad
- 100W, 100~240VAC auto-switch power supply



ACME PORTABLE

For more information, go to:
http://www.acmeportable.com

TRIDENT

Display

	Trident
Diagonal	3 x 17”, 5:4 Display
LCD Resolution	3 x 1280 x 1024
Brightness	300 nits
Contrast Ratio	500:1
Refresh Rate	60 Hz
Display Colors	16.2M colors

Specifications

	Trident
KVM Port	3x D-Sub 15 pins KB/Touchpad ports
Keyboard	105-key cherry keyboard with 2-button touchpad
Keyboard & Mouse Interface	USB
Viewing Angle	170° (H) x 160° (V)
Power	100W, 100-240VAC, 50/60Hz
Dimensions & Weight	5.19” x 17.21” x 23.41” (H x W x D) / 61 lbs
Compliance	CE, FCC, RoHS
Operating Temperature	0-50°C (32-122°F)

US - ACME Headquarters

ACME Portable Machines, Inc.
1330 Mountain View Circle, Azusa, CA
Tel: +1 (626) 610-1888
Fax: +1 (626) 610-1881
Email: sales@acmeportable.com

http://www.acmeportable.com

Germany - ACME Branch

ACME Portable Computer GmbH
Benzstrasse 15, 76185 Karlsruhe
Tel: +49 (0) 721-570 453-0
Fax: +49 (0) 721-570 453-29
Email: info@acmeportable.de

http://www.acmeportable.de

Taiwan - ACME Branch

ACME Portable Corp.
5F, No. 25, Wu Chuan 3rd Road,
Wu-Ku Ind. Park, New Taipei City, Taiwan
Tel: +886 (2) 2298-3636
Email: info@acmeportable.com.tw

http://www.acmeportable.com.tw