


# PCM-261

## LVDS/TTL to DVI Module



CE FCC

### Features

- Supports 18 and 24-bit LVDS to DVI
- Supports 18 or 24-bit TTL LCD to DVI (optional)

### Specifications

| General                      |                                            |
|------------------------------|--------------------------------------------|
| Chipset                      | Silicon® Image Sil 164; NS DS90CF364       |
| LCD Connector                | Hirose Output Connector; DVI               |
| Mechanical and Environmental |                                            |
| Dimension (L x W)            | 72 x 62 mm                                 |
| Weight                       | 0.029 kg (0.064 lb)                        |
| Operating Temperature        | 0 ~ 60° C (32 ~ 140° F)                    |
| Operating Humidity           | 0% ~ 90% relative humidity, non-condensing |
| Power                        |                                            |
| Power Supply Voltage         | +5 V, ±5%                                  |

### Packing List

1 x User's manual  
1 x PCM-261 board

### Ordering Information

| Standard             |                                       |
|----------------------|---------------------------------------|
| PCM-261L-A0A1E       | 24-bit LVDS to DVI Module             |
| PCM-261L-B0A1E       | 18-bit LVDS to DVI Module             |
| PCM-261T-A0A1E       | 24-bit TTL to DVI Module              |
| Optional Accessories |                                       |
| 1700000851           | 24-bit TTL to 24-bit TTL cable        |
| 1700000850           | 18-bit LVDS to 18-bit LVDS FOR 855GME |
| 1700000853           | 24-bit LVDS to 24-bit LVDS            |
| 1700000827           | 18-bit LVDS TO 18-bit LVDS            |