GHI-293

2U Rackmount Chassis









Specifications

- EIA RS-310C 19" Rackmount Standard
- Construction: Heavy Duty Cold Rolled Electroplated Steel
- Color: Black (Standard), Beige or Custom
- System Boards: Dual Xeon, Pentium 4, Athlon 64, Dual Opteron
- Support EATX M/B (Max. to 12" x 10.5") SSI EEB 3.0
- Drive Capacity: 2x 5.25" & 1x 3.5"FDD & 4x 3.5" Swappable Trays
- Drive Interface: PATA, SATA, SCSI320, Multilane SATA or SAS
- Power Supply (Optional): 2U Single up to 600W or 2U Redundant up to 500W ATX P/S(Rear Installation) Max. Depth 300mm
- Cooling: 3x (80mm = 42.5CFM ea.)Fans
- Front Door: Single Door With 2 Thumbscrews (Removable)
- Riser Card: GHP-R0301 (32bit Ribbon) or GHP-R0304 (64bit Ribbon) (Optional)
- Connector Port (Front): 2x USB Ports
- Expansion Slots(Optional): 2 or 3x Horizontal ISA/PCI/AGP Option Slots(GHI-293H) 7x Low Profile PCI Slots(GHI-293V)
- Indicators: LEDs for Power ON/OFF, 4xHDD Activity, Fan, Temperature, LAN
- Switch: Power ON/OFF Momentary (Pushbutton), System Reset, Buzzer Reset
- Dimensions (W x H x D): 483 x 88 x 560mm (19" x 3.5" x 22.1")
- Cuft: 3.3
- GW: 13.9kgs / 30.7lbs
- Carton Size(cm): 57.0 x 22.0 x 73.5 (22.4" x 8.7" x 28.9")
- Humidity: 5% - 95% Non-condensing

Dimension

