GHI-584

5U Rackmount Chassis





Specifications

- EIA RS-310C 19" Rackmount Standard
- Construction: Heavy Duty Cold Rolled Electroplated Steel
- Color: Black (Standard), Beige or Custom
- System Boards: Pentium 4, Dual Xeon, Athlon 64, Dual Opteron, Quad Opteron
- Supports EATX 2 Layer M/B (Max. to 13" x 16") With Removable Drawer
- Drive Capacity: 1x Slim CD-ROM, 1x Slim FDD & 24x 3.5" Hot Swappable & 2x 2.5" HDD & 2 x 3.5" HDD (Optional)
- Drive Interface: PATA, SATA, SCSI320, Multilane SATA or SAS
- Power Supply (Optional): 1U Redundant up to 1650W ATX P/S (Rear Installation) Max Depth 300mm
- Cooling: 6x (60mm = 23.5CFM ea.) Fans & 2x (120mm 90CFM ea.) Fans
- Front Door: Single Door With 2 Thumbscrews (Removable)
- Connector Port (Front): 2x USB Ports
- Thermal Management Card: GHA-CO04
- Indicators: LEDs for Power ON/OFF, HDD Activity, Fan, Temperature, LAN
- Flexible Hold Down Bar Designed
- Switch: Power ON/OFF Momentary (Dimple), System Reset, Buzzer Reset
- Dimensions (W x H x D): 483 x 222 x 650mm (19" x 8.7"" x 25.6")
- Cuft: 6.8
- GW: 34.5kgs / 76.1lbs
- Carton Size (cm): 85.5 x 37.0 x 61.0 (33.7" x 14.6" x 24.0")
- Humidity: 5% - 95% Non-condensing

Dimension

