

SK-102

102-Key NEMA 4X, Desktop Keyboard with Integrated HulaPoint™ Pointing Device



PS/2: SK-102-PS2
USB: SK-102-USB

IKEY Industrial Peripherals
2621 Ridgepoint Dr., Suite 235
Austin, TX 78754
800.866.6506 Telephone
512.837.0207 Fax

INDUSTRIAL RATINGS

NEMA 4, 4X [IP65]
UL-1950
CE
FCC Class 15, Part B

KEY SWITCH

MATERIAL: Industrial silicone rubber
LIFE: Greater than 10 million cycles
TRAVEL: 0.055" (1.4mm)
ACTUATION FORCE: 5 oz (130g)
FEEDBACK: Tactile with mechanical snap

POWER

KEYBOARD: 5V@20ma (from CPU port)
HULAPOINT: 5V@10ma (from mouse conn. port)

TEMPERATURE RANGE

-40F to +194F (-40C to +90C)

HUMIDITY: 100%Resistant

SHOCK: 3x11 ms pulses of 50g on each of 3 axes

VIBRATION

POWER SPECTRAL DENSITY: 0.04g/Hz
FREQUENCY RANGE: 20Hz - 2kHz
DURATION OF TEST PER AXIS: 3 hours

FLAMMABILITY

PRINTED CIRCUIT BOARD: 94 VO
SILICONE OVERLAY: 94 HB
INTERFACE CABLE: 94 VO

WEIGHT: 1.6 lbs (0.7 kg)

FEATURES

12 Function Keys
Microsoft Windows Key
Three Button Pointing Device
ABS-Polycarbonate Plastic Case
Secondary Legend Flexibility
Suitable For 19-inch Rack Applications

DIMENSIONS: (W-H-D) 14.5" x 5.5" x 0.83"
368.3mm x 139.7mm x 21.0mm

CABLE

LENGTH: 10 feet (3.94 meters)
DESIGN: "Y" Cable (providing separate keyboard and mouse connections),
Or Single-Cable USB

COMPATIBILITY

KEYBOARD: PS/2, USB, Windows, and NT
HULAPOINT: Microsoft, PS/2, Serial, and Logitech

WARRANTY: 1 Year Limited Warranty

