

RDC-5K

116 Key Rackmount NEMA 12 Keyboard with Integrated HulaPoint™ Pointing Device



IKEY Industrial Peripherals
2621 Ridgpoint Dr., Suite 235
Austin, TX 78754
800.866.6506 Telephone
512.837.0207 Fax

INDUSTRIAL RATINGS

NEMA 12
UL-1950
CE
FCC Class 15, Part B

KEY SWITCH

MATERIAL: Industrial silicone rubber
LIFE: Greater than 10 million cycles
TRAVEL: 0.060" (1.5mm)
ACTUATION FORCE: 5 oz (130g)
FEEDBACK: Tactile with mechanical snap

POWER

KEYBOARD: 5V@10ma (from CPU port)
HULAPOINT: 5V@10ma (from mouse conn. port)

TEMPERATURE RANGE

-40F to +194F (-40C to +90C)

HUMIDITY: 80%

SHOCK: 3x11 ms pulses of 50g on each of 3 axes

VIBRATION

POWER SPECTRAL DENSITY: 0.04g/Hz
FREQUENCY RANGE: 20Hz - 2kHz
DURATION OF TEST PER AXIS: 3 hours

FLAMMABILITY

PRINTED CIRCUIT BOARD: 94 VO
SILICONE OVERLAY: 94 HB
INTERFACE CABLE: 94 VO

SLIDE LOAD RATING: 130 lbs/pair

FEATURES

20 Function Keys
Three Button Pointing Device
Black Polane Epoxy Paint
Chrome Plated Ball Bearing Slides

DIMENSIONS:

Pull Slot: (W-H-D) 19" x 15" x 1U (1.75")
T-Handle (W-H-D) 19" x 17" x 1U(1.75")

CABLE

LENGTH: 10 feet (3.94 meters)
DESIGN: "Y" Cable (providing separate keyboard and mouse connections)

COMPATIBILITY

KEYBOARD: PS/2, USB, AT, Windows, and NT
HULAPOINT: Microsoft, PS/2, Serial, and Logitech

WARRANTY: 1 Year Limited Warranty

