

PM-88

Small-Footprint Industrial Keyboard

The PM-88 is a small-footprint keyboard that meets harsh use standards. It has 88 full-size keys with embedded notebook key functions. The PM-88 is a perfect fit for industrial, kiosk or mobile computing needs. Constructed in a small-footprint compact case, the PM-88 allows for space saving and mobility, and includes a secondary legend accessed with the NumLock and Fn key.



Technical Specifications

Certifications

NEMA 4X, CE
UL60950, FCC Part 15 Class B

Key Switch

MATERIAL: Industrial silicone rubber
LIFE: 10 million cycles
TRAVEL: 0.055
ACTUATION FORCE: 200g (+/- 20g)
FEEDBACK: Tactile with mechanical snap

Power

PS/2: 50mA@5V (from Keyboard port)
USB: 50mA@5V (from CPU port)

Temperature Range

STORAGE: -40C to +90C
OPERATING: -40C to +70C

Humidity

100% (when properly installed)

Shock

3x11 ms pulses of 50g on each of 3 axes

Vibration

POWER SPECTRAL DENSITY: 0.04g/Hz
FREQUENCY RANGE: 20Hz - 2 kHz
DURATION OF TEST PER AXIS: 3 hours

Flammability

PRINTED CIRCUIT BOARD: 94 VO
SILICONE OVERLAY: 94 HB
INTERFACE CABLE: 94 VO

Weight

2 lbs (0.92 kg)

Dimensions

11.80" x 6.80" x 0.62" (w-h-d)
300mm x 172.7mm x 38.1mm
CUTPIT: 10.40" x 5.40"

Cable

LENGTH: 4 feet coiled (1.2 m)
DESIGN: PS/2 or Single-Cable USB

Compatibility

PS/2 KEYBOARD: All Windows Operating Systems

Warranty

1 year limited warranty

Model Numbers

PM-88-PS2: With PS/2 cable
PM-88-USB: With USB cable

Features and Benefits

- 11.80" x 6.80" x 0.62" (w-h-d)
- 12 Function Keys
- 88-Key Functionality
- ABS Polycarbonate Frame
- USB and PS/2 configurations available