

SL-75

Compact Backlit Industrial Keyboard

iKey's SL-75 keyboard provides a perfect option for in-vehicle computer systems and other portable environments. Its backlit keys are ideal for low-light environments. They operate by pressing the light bulb key located in the keyboard's upper-right corner. This unit offers a compact solution for dirty, wet and dusty environments. It provides full keyboard functionality with 75 keys and 12 function keys.



Technical Specifications

Certifications

NEMA 4X
UL60950, FCC Part 15 Class B

Key Switch

MATERIAL: Industrial silicone rubber
LIFE: 10 million cycles
TRAVEL: 0.055
ACTUATION FORCE: 200g (+/- 20g)
FEEDBACK: Tactile with mechanical snap

Power

KEYBOARD: 5V@ 10 ma (from CPU port)

Temperature Range

STORAGE: -40C to +90C
OPERATING: -40C to +70C

Humidity

100%

Shock

3x11 ms pulses of 50g on each of 3 axes

Vibration

POWER SPECTRAL DENSITY: 0.04g/Hz
FREQUENCY RANGE: 20Hz - 2 kHz
DURATION OF TEST PER AXIS: 3 hours

Flammability

PRINTED CIRCUIT BOARD: 94 VO
SILICONE OVERLAY: 94 HB
INTERFACE CABLE: 94 VO

Weight

3 lbs (1.38 kg)

Dimensions

8.25" x 4.3" x 1.05" (w-h-d)
209.6mm x 111.3mm x 26.7mm

Cable

LENGTH: 10 feet (3 meters)
DESIGN: PS/2, AT or Single-Cable USB

Compatibility

PS/2 KEYBOARD/HULAPOINT: All Windows Operating Systems
USB KEYBOARD/HULAPOINT: All Windows and Macintosh OS

Warranty

1 year limited warranty

Model Numbers

SL-75-PS2: With PS/2 cable
SL-75-USB: With USB cable
SL-75-STD: With AT

Features and Benefits

- 8.25" x 4.3" x 1.05" (w-h-d)
- 0.375-Inch Keycaps with .50-Inch Spacing
- Aluminum Enclosure
- AT/Serial, PS/2 and USB or configurations available
- Red Backlit Keys