iKey

input iKey. output success.

2621 Ridgepoint Drive, Suite 235 Austin, TX 78754 1.800.866.6506 www.ikey.com

FP15-PM

15-inch Panel Mount Display

iKey's line of high-quality, compact TFT flat panel displays are ideal solutions for industrial computing environments. Our flat panel displays can be easily integrated into new or existing systems. The new FP15-PM features 350 nits of brightness and a stainless steel front bezel. It is rated NEMA 4X, making the unit a durable solution that resists corrosion, dust, water and ice. Menu items such as brightness and contrast are easily accessed on the back of the display.



Technical Specifications

Power
35 Watts

Temperature Range
OPERATING: 0°C to 50°C
STORAGE: -20°C to 60°C

Weight
22 lbs (10.12 kg)

Dimensions
MAXIMUM OUTER DIMENSIONS
(W-H-D) 17.72" x 14.595" x 2.057"
449.6mm x 371.6mm x 78.2mm
CUTOUT DIMENSIONS
(H-V) 16.45" x 13.38"
417.8mm x 339.9mm
VIEWING ANGLE
(H-V) 160° x 160°

Cable
MONITOR: 15 Pin video cable
TOUCHSCREEN: 9 Pin serial

Compatability
MONITOR: DOS, Windows 95, NT, 98, 2000
TOUCHSCREEN: DOS, Windows 95, NT, 98, 2000
BACKLIGHT LIFE: 40,000 hours

Warranty
1 Year Limited Warranty

Model Numbers
FP15-PM: Flat Panel Display
FP15-PMT: Flat Panel Display with Touchscreen

Features and Benefits

- Stainless Steel Case
- 15.1-inch display screen
- 17.72" x 14.595" x 2.057"
- Stainless Steel Bezel
- Display Format: 1024 x 768 pixels
- Analog Color
- Screen Size: 15.1" (384mm) Diagonal
- Screen Synchronization: Autosync
- Contrast Ratio: 200:1
- Color: 16.7M
- Brightness: High-Bright 200 nits
- Plug and Play: DDC1/DDC2B

©2008 iKey, Ltd. All rights reserved.