



SSP5675-INU

56.7" Resizing LCD, 1000 nits LED backlight, 3840 x 537 ultra-wide aspect ratio 16:2.2

The SSP5675-INU is a 56.7 inch color TFT-LCD display with special aspect ratio 16:2.2 and wide resolution 3840 x 537. It is Litemax's Spanpixel series product which designed for high brightness 1000 nits with power efficiency LED backlight. It provides LCD panel with specific aspect ratios and sunlight readable for digital signage, public transportation, exhibition hall, department store, and vending machine.

Key Features

- Resizing LCD
- Ultra-Wide Screen (16 : 2.2)
- High Brightness 1000 nits
- Sunlight Readable
- LED Backlight
- Slim Bezel
- BL MTBF: 100,000 hours



Specifications

Model Name	SSP5675-INU
Description	56.7" Resizing LCD, 1000 nits LED backlight, 3840x537
Screen Size	56.7"
Display Area (mm)	1428.48(H) x 199.8(V)
Brightness	1000 cd/m ²
Resolution	3840x537
Aspect Ratio	16 : 2.2
Contrast Ratio	6000 : 1
Pixel Pitch (mm)	0.374(H) x 0.374(V)
Pixel Per Inch (PPI)	67
Viewing Angle	178°(H), 178°(V)
Color Saturation (NTSC)	82%
Display Colors	1.07G
Response Time (Typical)	9.5ms
Panel Interface	V-by-one
AD Board Input Interface	VGA, DVI-D, HDMI, DP
AD Board Input Power	DC12V
Power Consumption	71.1W, (76.1W with AD Board)
OSD Key	5 Keys (Power Switch, Menu, +, Exit, -)
OSD Control	Brightness, Color, Contrast, Auto Turing, H/V Position...etc
Dimensions (mm)	1462.5x 233.8 x 29.7
Bezel Size(U/B/L/R)	14.5/14.5/14.5/14.5 mm
Weight (Net)	6.4 kg
Operating Temperature	0 °C ~ 50 °C
Storage Temperature	-20 °C ~ 60 °C

SSF= Panel+ LED Driving Board

SSH= Panel+ LED Driving Board + AD Control Board

Specifications are subject to change without notice.

All brands or product names are trademarks or registered trademarks of their respective companies.




Mechanical Drawing


Outline Dimensions



Unit: mm

Note :

1. THE DIMENSION EXCLUDES DEFORMATION.
2. MODULE THICKNESS TO BE 29.7 MAX.(with LID Cover)
3. LED B/L CONNECTOR : HD2505-02 OR COMPATIBLE
4. I/F CONNECTOR TO BE JAE FI-R51S-HF OR COMPATIBLE
5. M4 USER HOLE SCREW TORQUE 5.0 kgf- cm MAX , HOLE Depth 6.7mm Max.







Connector View



Ordering Information

Part Number	Description
SSF5675-INU-A01	56.7",1000nits,3840*537.LID56A,3in1,V1
SSH5675-INU-M01	56.7",1000nits,3840x537,LID56A,AD9131GDPH,DC12V,3in1,V1

Optional Accessories

Part Number	Description
840612071200	ADAPTER,12V,7A,84W.FSP084-DIBAN2.POWER DIN 4P,P
810618301010	CABLE.POWER.AC.1830mm USA type
810618301090	CABLE,POWER,AC,1830mm Europe type
810618301050	CABLE.POWER.AC.1830mm UK type
810618301170	CABLE.POWER,AC,1830mm Australia type
810618301031	CABLE.POWER.AC.1830mm Japan type

By Customer Request

Glass	Tempered glass, AR coating.....
-------	---------------------------------