

3425 Specifications



Fanless Embedded Controller

Model Number	REC3425
System	
Processor	Intel Core 2 Duo/ Core Duo/ Celeron M (65nm) Processors
Chip Set	Intel 945GME + ICH7M
System Memory	200-pin DDRII SODIMM x 1, Max. 2GB (DDRII 400/533/667)
Ethernet	Intel 82573L, 10/100/1000Base-TX, RJ-45x1
Storage	Compact Flash x 1; SATA II HDD x 1
Audio	Line-Out, MIC in
I/O Interface- Front	PWR/HDD LED, Power on SW, PS/2 Keyboard & Mouse RJ45 x1, USB x2, COMx1, VGAx1
I/O Interface- Rear	Audio Phone Jack (Line-out, MIC-in), USBx2, COMx1 (RS232/422/485 x1), DC Input Phoenix Connector
BIOS	Award Plug & Play BIOS- 1MB ROM
Wake On LAN	Yes
Watchdog Timer	Generates a time-out system reset
H/W Status Monitor	Supports power supply voltages, Fan speed and temperature monitoring
Extension Interface	Mini PCI x 1 (internal)
Power Requirement	+12V Only, AT/ATX or +9~36V Wide Range DC Input (optional)
Display	Supports CRT/LCD, CRT/TV, LCD/TV, simultaneous/ Dual view displays
Chip Set	Intel 945GME Integrated
Memory	Shared system memory up to 224MB/DVMT3.0
Resolutions	Up to 2048 x 1536 @ 32bpp for CRT Up to 1280 x 1024 @ 36bpp for LCD
Mechanical	
Construction	Rugged Aluminum Alloy Chassis
Mounting	Wallmount, Desktop
Dimension	196(W) x 64(H) x 150 (D) mm
Net Weight	2.3kg
Environmental	
Operating Temperature	-15 C~55 C (5 F~131 F)-CFD -20 C~70 C (-4 F~158 F) 5~90% @ 40 C, non-condensing
Storage Temperature	5g rms / 5~500Hz / random operation-CFD
Operating Humidity	50g peak acceleration (11msec. duration)-CFD
Certification	Design to meet CE/FCC class A, IEC60945 BV Marine Approval

Specifications are subject to change without notice. All brands or product names are trademarks or registered trademarks of their respective companies.