


REC5415

Specifications



Fanless Embedded Controller

Model Number	REC5415
System	
Processor	Intel® Core™ 2 Duo / Celeron® M
Chip Set	Intel® 945GME + ICH-7M
System Memory	DDRII SODIMM x 1, Max. 2GB (DDRII 400/533/667)
Ethernet	Intel® EP82562ET, 10/100 Base-TX; Intel 82573 GbE (Gigabit Ethernet)
Storage	Compact Flash x1
Audio	ALC655, Line-Out, MIC
I/O Interface- Front	PWR/HDD LED, DC-In, Power on SW, PSII KB/MS, RJ45 x2, USB x4, COMx2 (RS232 x1, RS232/422/485 x1)
I/O Interface- Rear	Audio Phone Jack (Line-out, MIC-in), LVDS Connector, CF Slot, DVI-I, HDMI (Optional)
BIOS	Award
Wake On LAN	Yes
Watchdog Timer	Generates a time-out system reset
H/W Status Monitor	Supports power supply voltages, fan speed and temperature monitoring
Extension Interface	Mini PCI (internal); Mini PCI-E (internal)
Power Supply	DC Input: Internal DC-DC Converter; Input voltage: 9V DC ~ 36V DC
Display	Supports CRT/LCD, Dual Simultaneous Display
Display Chip Set	Intel® 945GME Integrated
Memory	Shared system memory up to 224MB
Resolutions	Up to 2048x 1536 (QXGA) for CRT; Up to 1600x 1200 (UXGA) for LCD
Mechanical	
Construction	Rugged Aluminum Alloy Chassis
Mounting	Wallmount, Desktop, DIN Rail
Dimension	262mm (W) x 61mm(H) x 184mm(D)
Net Weight	4kg
Environmental	
Operating Temperature	-15°C~55°C (5°F~131°F)-CFD
Storage Temperature	-20°C~70°C (-4°F~158°F)
Operating Humidity	5~90% @ 40°C, non-condensing
Certification	CE/FCC



Specifications are subject to change without notice. All brands or product names are trademarks or registered trademarks of their respective companies.