

Graphic OIT

Silver Series

HMI5056N



**5.6" 65K Color TFT LCD Touchscreen
with advanced features**



- 320 x 234 Pixel High Def. TFT display
- Bright 65,536 (16-bit) Colors
- 400 MHz CPU, 128 MB Flash, 64 MB DRAM
- TrueType fonts and international characters
- Data logging/Data sampling
- Online/offline simulation
- Multi-language feature
- Alarm and recipe management
- Animation and popup windows
- 2 year warranty

The Silver Series HMI5056N is a rugged graphic operator interface with a high resolution 5.6" diagonal touchscreen TFT display. The nominal 2" depth with port access along the bottom of the OIT makes mounting in tight spots easy. The fanless design means no extra space for cooling is required.

You can easily give your system a professional look with this vivid display, extensive graphics libraries,

and the ability to import custom BMPs, JPGs, or animated GIFs. It is the perfect operator interface solution for your industrial



applications whether process control, packaging, water treatment, building automation, assembly line controls and many others.

The HMI5056N is reliable, affordable, loaded with features, and easy to use. It is another smart solution from the operator interface experts.

**Every Machine
Needs the
Human Touch**



www.maplesystems.com

HMI5056N Specifications

Hardware	
CPU Type	400MHz 32-bit RISC Fanless
Memory	128MB Flash, 64MB DRAM
Serial Ports	Com1: RS-232/RS-485, 2 or 4 wire
USB Interface	Client only
RTC	Built-in

Display	
Type	5.6" TFT color
Size (WxH)	4.5 x 3.5 inches [114 x 89 mm] 5.6" diagonal
Resolution (pixels)	320 x 234
Brightness (cd/m ²)	300
Contrast ratio	300:1
Max Colors	65536 (16 bit)
Viewing Angle (°)	45/65/65/65 (T,B,R,L)
Backlight Longevity	30,000 hrs (LED backlight)

Touchscreen	
Type	4 wire analog resistive
Resolution	Continuous
Light Transmission	Above 80%
Lifespan	1 million activations minimum

Environmental	
Operating Temperature	14 ~ 113°F (-10 ~ 45°C)
Storage Temperature	-13 ~ 158°F (-25 ~ 70°C)
Relative Humidity	10% ~ 90% (non-condensing)
Shock (operation)	10 to 25Hz (X,Y,Z direction, 2G, 30 minutes)
Ratings	IP65, NEMA4, NEMA4X (indoor only)
Certifications	CE, EMI FCC Class A, cULus pending

Specifications subject to change without notice.

Functionality	
Data Transfer	Share data between HMIs and PLCs
Data Logging/Sampling	Up to 1000 records Time/Trigger-based
Windows Fonts	Unicode support International characters
Multiple Languages	Up to 8 languages per object
Security	6 levels, 3 passwords per level Interlock Safety feature Visibility protection
Macros	Math functions, 32-bit Float support
Recipe Management	Up to 32,767 records Index Feature
Alarm Management	Four priority levels Organize by category Real-Time or History
Trending	Up to 20 channels Real-Time or History Watch Line Feature
Ease of Use	Popup windows Offline/Online Simulation Extensive Graphics Libraries


Mechanical	
Enclosure	Plastic molding
Dimensions (WxHxD)	8.03 x 5.91 x 1.94 inches [204 x 150 x 49 mm]
Panel Cutout Dim. (WxH)	7.56 x 5.43 inches [192 x 138 mm]
Weight	1.9 lbs [0.86 kg]
Mounting	Panel
Power Requirements	24VDC $\pm$ 20% 250mA
Warranty	2 years

Order Number	
HMI5056N	5.6" TFT Graphic OIT




808 134th St SW, Suite 120
Everett, WA 98204
425.745.3229 • 425.745.3429 (fax)
maple@maple-systems.com
www.maplesystems.com


HMI5056N Dimensions



Front View



Rear View



Bottom View

- A Fuse
- B Power Connector
- C Dust Cover
- D Com Port DB9S
- E Com Port DB9P
- F USB Client Only

Dimensions in inches [mm]