

CPCI to CPCI Serial Hybrid Rack for Single Eurocards

- **19" rack-mountable**
- **IEEE 1101.10/11 compliance**
- **4U / 84 HP system (incl. 1U fan tray)**
- **8-slot hybrid backplane**
- **CompactPCI® PlusIO system slot**
- **4 CompactPCI® Serial (PICMG CPCI-5.0) peripheral slots to the right**
- **3 CompactPCI® peripheral slots to the left**
- **All slots prepared for rear I/O**
- **250 W Plug-in PSU 90..264 VAC**
- **44HP space for individual extensions**
- **For MEN SBCs F11S, F12N, F14, F15, F17, F18, F19P, F21P, F50P, F75P**



This compact 4U rack-mount enclosure is a basic system that allows the configuration with both CompactPCI® Serial and CompactPCI® cards. Being a hybrid system, it offers an uncomplicated and cost-effective migration solution from parallel 3U CompactPCI® to serial CompactPCI® Serial via the CompactPCI® PlusIO standard.

The 8-slot hybrid backplane in this configuration does not need a bridge or an active logic. The four slots on the left are designed for 32-bit CompactPCI® and rear I/O on P2. The four slots on the right are reserved for CompactPCI® Serial. The CompactPCI® PlusIO system slot is the fourth slot from the left. Either a standard CompactPCI® 2.0 or a PICMG 2.30 CompactPCI® PlusIO CPU board can be used in this slot.

This hybrid system is designed for use with the MEN system-slot SBCs F11S, F12N, F14, F15, F17, F18, F19P,

F21P and F50P. Only F19P, F21P and F50P support CompactPCI® Serial. That way, the three remaining slots on the CompactPCI® bus and the four CompactPCI® Serial slots can be used to install additional I/O functions.

While the CompactPCI® Serial slots on the right are best suited for functions like Gigabit Ethernet, 10 Gigabit Ethernet or high end graphic with high data rate requirements, the parallel CompactPCI® bus delivers enough performance for all kinds of conventional I/O like binary or analog signals.


In addition, the system offers space for mass storage devices.

A 8HP plug-in 250W power supply unit which is accessible at the back of the system is already included and wired.

The enclosure meets EMC requirements, making it a perfect choice for embedded applications in harsh environments.


Ask us for completely configured, wired and tested systems!

Diagram



Backplane

PICMG 2.0 Periph. Rear IO	PICMG 2.0 Periph. Rear IO	PICMG 2.0 Periph. Rear IO	PICMG 2.0 PICMG 2.30 System Slot	PICMG CPCI-S.0 Periph.	PICMG CPCI-S.0 Periph.	PICMG CPCI-S.0 Periph.	PICMG CPCI-S.0 Periph.
---------------------------------	---------------------------------	---------------------------------	---	---------------------------	---------------------------	---------------------------	---------------------------



Technical Data

General System Characteristics	■ Compliance with IEC 60 297-3, IEEE 1101.10 ■ 8 slots for 3U Eurocard boards (4 CompactPCI® Serial slots)
Mechanical Specifications	■ 19" rack-mount standard ■ 3U card vertical ■ Dimensions: 3U, 84HP, 278mm depth ■ Weight: tbd.
CompactPCI®/CompactPCI® Serial Backplane	■ 8-slot ■ CompactPCI® PlusIO system slot on the fourth slot from the left □ Support of four CompactPCI® Serial peripheral slots ■ Three CompactPCI® peripheral slots ■ Four CompactPCI® Serial peripheral slots
Power Supply	■ Plug-in power supply □ 3U/8HP □ 250W □ 90V..264V AC wide range □ 3.3 V/40A, 5 V/40A, 12V/5.5A, -12 V/2A □ 3U power backplane with P47 receptacle □ 3U power input module with IEC input, fuse holder, line filter and power switch ■ Power connector and power-on switch at the back
1U fan chassis	■ Two vertical fans □ 12V □ Air flow volume 140 m³/h (manufacturer's data) □ Dimensions 119 x 119 x 32 mm □ Sound pressure level 39 dB(A)
Environmental Specifications	■ Temperature range (operation): □ 0..+50°C ■ Temperature range (storage): □ -40..+85°C □ Power supply: -20..+65°C without derating ■ Relative humidity (operation): max. 95% non-condensing ■ Relative humidity (storage): max. 95% non-condensing ■ Altitude: -300m to + 3,000m ■ Shock: 15g/11ms ■ Bump: 10g/16ms ■ Vibration (sinusoidal): 2g/10..150Hz
EMC	■ Tested according to EN 55022 (radio disturbance), IEC1000-4-2 (ESD) and IEC1000-4-4 (burst)
Suited for MEN Boards...	■ F11S - 3U CompactPCI® Intel® Atom™ SBC ■ F12N - CompactPCI® MPC5200B SBC ■ F14 - CompactPCI® Pentium® M SBC ■ F15 - CompactPCI® Core Duo SBC ■ F17 - CompactPCI® Core 2 Duo SBC ■ F18 - CompactPCI® Core 2 Duo SBC ■ F19P - CompactPCI® PlusIO Core 2 Duo SBC ■ F21P - CompactPCI® PlusIO Intel® Core™ i7 SBC ■ F50P - CompactPCI® PlusIO MPC8548 SBC ■ F75P - CompactPCI® PlusIO Intel® Atom™ Safe Railway Computer

Ordering Information

Standard CPCI to CPCI Serial Hybrid Rack for Single Eurocards Models	MEN delivers turn-key systems completely installed (hardware, operating system, accessories), wired and tested. Different rack sizes, power supplies and backplanes on request. For details please contact your local sales representative.	
	0701-0056	CompactPCI® 19" 4U/84HP rack-mount enclosure for 3U cards (vertical), 4+4-slot 3U CompactPCI® / CompactPCI® Serial hybrid backplane, prepared for rear I/O, 250W power supply wide range 90..264VAC on rear, 1U fan tray with 2 fans included, 0..+60°C
Miscellaneous Accessories	0714-0009	Filler panel 3U/4HP, IEEE1101, textile gasket
	0714-0018	Filler panel 3U/8HP, EMC gasket, fully pre-mounted
	0714-0019	Filler panel 3U/12HP, EMC gasket, fully pre-mounted

Contact Information

Germany

MEN Mikro Elektronik GmbH
Neuwieder Straße 3-7
90411 Nuremberg
Phone +49-911-99 33 5-0
Fax +49-911-99 33 5-901

info@men.de
www.men.de

France

MEN Mikro Elektronik SA
18, rue René Cassin
ZA de la Châtelaine
74240 Gaillard
Phone +33 (0) 450-955-312
Fax +33 (0) 450-955-211

info@men-france.fr
www.men-france.fr

USA

MEN Micro, Inc.
24 North Main Street
Ambler, PA 19002
Phone (215) 542-9575
Fax (215) 542-9577

sales@menmicro.com
www.menmicro.com

The date of issue stated in this data sheet refers to the Technical Data only. Changes in ordering information given herein do not affect the date of issue. All brand or product names are trademarks or registered trademarks of their respective holders.

MEN is not responsible for the results of any actions taken on the basis of information in the publication, nor for any error in or omission from the publication.

MEN expressly disclaims all and any liability and responsibility to any person, whether a reader of the publication or not, in respect of anything, and of the consequences of anything, done or omitted to be done by any such person in reliance, whether wholly or partially, on the whole or any part of the contents of the publication.

The correct function of MEN products in mission-critical and life-critical applications is limited to the environmental specification given for each product in the technical user manual. The correct function of MEN products under extended environmental conditions is limited to the individual requirement specification and subsequent validation documents for each product for the applicable use case and has to be agreed upon in writing by MEN and the customer. Should the customer purchase or use MEN products for any unintended or unauthorized application, the customer shall indemnify and hold MEN and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim or personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that MEN was negligent regarding the design or manufacture of the part.

In no case is MEN liable for the correct function of the technical installation where MEN products are a part of.

Copyright © 2013 MEN Mikro Elektronik GmbH. All rights reserved.