

P507 – Quad RS422/485 Interface PMC

- **32-bit/33-MHz PMC**
- **4 high-performance UARTs**
- **Full and half duplex, software programmable**
- **Serial data rates up to 921 600 bit/s**
- **Isolation between channels**
- **-40 to +85°C with qualified components**




The P507 is a high-performance quadruple UART with RS422/485 interface. It supports full duplex (with RS422) and half duplex operation (with RS485) and data rates of up to 921,600 bit/s. Each channel has its own 500 V isolation, with all ports being available on the 50-pin D-Sub front connector.

The P507 is based on the USM™ concept. USM™ Universal Submodules make PMC modules more flexible than ever. The UART interfaces are realized via

four IP cores implemented inside its onboard FPGA. This function can be changed at any time through implementation of different IP cores. The corresponding line drivers are realized on the USM™ which is simply plugged on the P507.

The I/O mezzanine module is suitable for any PMC compliant host carrier board in any type of bus system, i.e. CPCI, VME or on any type of stand-alone SBC in telecommunication, industrial, medical, transportation or aerospace applications. It offers long-term availability for at least 10 years and is qualified for operation in the extended temperature range.

Diagram



Technical Data

UART Interfaces	■ Four RS422/RS485 UARTs ■ Software-configurable ■ Data rates up to 921,600 bit/s ■ 60-byte transmit/receive buffer ■ Full-duplex operation with RS422, half-duplex operation with RS485 ■ Isolation between channels: 500V ■ Compatible with 16550 UART
Memory	■ 32MB SDRAM memory □ Soldered □ DDR2 □ 132MHz memory bus frequency □ FPGA-controlled ■ 2MB non-volatile Flash □ For FPGA data and Nios® firmware □ FPGA-controlled
FPGA	■ Standard factory FPGA configuration: □ Main bus interface □ Interrupt controller, SMBus controller □ 16Z125_UART - UART Controller □ 16Z043_SDRAM - SDRAM controller □ 16Z045_FLASH - Flash interface □ 16Z034_GPIO - GPIO controller ■ The FPGA offers the possibility to add customized I/O functionality. See FPGA.
PMC Characteristics (PCI)	■ Compliant with PCI Specification 2.2 ■ 32-bit/33-MHz, 3.3V V(I/O) ■ Target
Peripheral Connections	■ Via front panel on a shielded 50-pin HP D-Sub SCSI 2 receptacle connector
Electrical Specifications	■ Isolation voltage: □ 500 VAC ■ Supply voltage/power consumption: □ +5V (-3%/+5%), 120mA □ +3.3V (-5%/+5%), 9mA
Mechanical Specifications	■ Dimensions: conforming to IEEE 1386.1 ■ Weight: 78g
Environmental Specifications	■ Temperature range (operation): □ -40..+85°C (qualified components) □ Airflow: min. 1.0m/s ■ Temperature range (storage): -40..+85°C ■ Relative humidity (operation): max. 95% non-condensing ■ Relative humidity (storage): max. 95% non-condensing ■ Altitude: -300m to + 3,000m ■ Shock: 15g/11ms ■ Bump: 10g/16ms ■ Vibration (sinusoidal): 1g/10..150Hz ■ Conformal coating on request
MTBF	■ 1 152 181 h @ 40°C according to IEC/TR 62380 (RDF 2000)
Safety	■ PCB manufactured with a flammability rating of 94V-0 by UL recognized manufacturers
EMC	■ Conforming to EN 55022 (radio disturbance), IEC1000-4-2 (ESD) and IEC1000-4-4 (burst)

Technical Data

Software Support

- Windows®
- Linux
- [For more information on supported operating system versions and drivers see Downloads.](#)

FPGA

This product offers the possibility to add customized I/O functionality in FPGA.

Flexible Configuration

- Customized I/O functions can be added to the FPGA.
- It depends on the board type, pin counts and number of logic elements which IP cores make sense and/or can be implemented. Please contact MEN for information on feasibility.
- [You can find more information on our web page "User I/O in FPGA"](#)

FPGA Capabilities

- FPGA Altera® Cyclone® II EP2C35
 - 33,216 logic elements
 - 483,840 total RAM bits
 - Supports Nios® II soft processor
- Connection
 - Functions can be linked to Wishbone or Avalon® bus
 - Available pin count: 46 pins (FPGA to USM™)
 - Functions available via USM™ at front I/O connector
- [MEN offers a USM™ development kit and an FPGA Development Package as well as Flash update tools for different operating systems.](#)

Configuration & Options

Standard Configurations

Article No.	Main FPGA Content	Soft Core	Memory	Signals	Cooling Method	Operation Temperature
15P507-00	4 RS422/485 interfaces	No	32 MB RAM, 2 MB Flash	Front	Convection	-40...+85°C

Options

CPU	■ Nios® soft core implementation possible (e.g. for real-time Ethernet)
Rear I/O	■ Via Pn4 rear I/O connector
Cooling	■ Conduction Cooling

Please note that some of these options may only be available for large volumes. Please ask our sales staff for more information.

Ordering Information

Standard P507 Models	15P507-00	Quad RS422/485 interface, 4 UART cores, front I/O, for convection cooled systems, -40...+85°C with qualified components
Miscellaneous Accessories	05P000-01	25 mounting screw sets to fix PMC/XMC modules on carrier boards
Software: Linux	This product is designed to work under Linux. See below for potentially available separate software packages from MEN.	
	13Z017-06	MDIS5™ low-level driver sources (MEN) for 16Z034_GPIO and 16Z037_GPIO
	13Z025-90	Linux native driver (MEN) for 16Z025_UART, 16Z057_UART and 16Z125_UART
Software: Windows®	This product is designed to work under Windows®. See below for potentially available separate software packages from MEN.	
	10Y000-78	Windows® Embedded Standard 7 BSP for F11S, F19P, F21P, G20, XM1L, XM2, MM1, MM2, SC21, SC24, SC27, BC50M, F206, F210, F215, F216, G215, P506, P507 and P511
	13P507-77	Windows® Installset (MEN) for P507 (Includes all free drivers developed by MEN for the supported hardware.)

For operating systems not mentioned here [contact MEN sales](#).

Documentation	Compare Chart mezzanine functions on PMC/XMC and PC-MIP® » Download	
	20P507-00	P507 User Manual

Contact Information

Germany

MEN Mikro Elektronik GmbH
Neuwieder Straße 3-7
90411 Nuremberg
Phone +49-911-99 33 5-0
Fax +49-911-99 33 5-901

info@men.de
www.men.de

France

MEN Mikro Elektronik SA
18, rue René Cassin
ZA de la Châtelaine
74240 Gaillard
Phone +33 (0) 450-955-312
Fax +33 (0) 450-955-211

info@men-france.fr
www.men-france.fr

USA

MEN Micro, Inc.
24 North Main Street
Ambler, PA 19002
Phone (215) 542-9575
Fax (215) 542-9577

sales@menmicro.com
www.menmicro.com

The date of issue stated in this data sheet refers to the Technical Data only. Changes in ordering information given herein do not affect the date of issue. All brand or product names are trademarks or registered trademarks of their respective holders.

MEN is not responsible for the results of any actions taken on the basis of information in the publication, nor for any error in or omission from the publication.

MEN expressly disclaims all and any liability and responsibility to any person, whether a reader of the publication or not, in respect of anything, and of the consequences of anything, done or omitted to be done by any such person in reliance, whether wholly or partially, on the whole or any part of the contents of the publication.

The correct function of MEN products in mission-critical and life-critical applications is limited to the environmental specification given for each product in the technical user manual. The correct function of MEN products under extended environmental conditions is limited to the individual requirement specification and subsequent validation documents for each product for the applicable use case and has to be agreed upon in writing by MEN and the customer. Should the customer purchase or use MEN products for any unintended or unauthorized application, the customer shall indemnify and hold MEN and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim or personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that MEN was negligent regarding the design or manufacture of the part.

In no case is MEN liable for the correct function of the technical installation where MEN products are a part of.

Copyright © 2013 MEN Mikro Elektronik GmbH. All rights reserved.