

65 KEY "OPERATOR KEYBOARD" WITH 38 mm TRACKBALL

Sealing IP65 static; PS/2 or USB compatible
10 relegendable keys

• GENERAL DESCRIPTION

This 65 key keyboard features all function- control- and numeral- keys as direct access keys in UNSHIFT and SHIFT mode. The complete upper and lower case alphabet is obtained in the ALPHA mode (status indicated by a green led). Ten extra control functions are available as relegendable keys (preprinted C1 to C10). In standard mode (ALPHA Lock OFF) C1 to C10 stands for the keycodes "CTRL" + "F1" to "CTRL" + "F10". In ALPHA mode (ALPHA Lock ON) C1 to C10 stands for the keycodes "ALT" + "F1" to "ALT" + "F10". For re-labelling by the final customer, see the instructions on the backside of this datasheet.

This keyboard is to be used with the standard US keyboard driver.

The 38 mm diameter industrial trackball provides accurate and precise cursor control.

The built-in seals provide an IP65 static (ball in rest) protection grade.

Enclosed

The complete unit will fit into 19" drawers (1HU) or can be used as table model.



dim: 328x204x42 mm
weight: 2,1 kg

Panel mount

For front panel mounting by means of six M4-threaded studs.

Operation of keyboard and trackball is possible at **all angles** (from horizontal to vertical).

A metal cover on the backside protect the mechanical- and electronical parts.

The front is sealed to IP65 static (ball in rest).



dim: 314x180x42 mm
weight: 1,2 kg

