

Dual-colour panel indicators

K3MA SERIES

excellent visibility and precise read-out

Advanced Industrial Automation



Actual size: 1/8 DIN (96x48 mm)

 Process






 Temperature

 Frequency & Rate

Clear precise information on process, temperature and frequency/rate applications.

- | | |
|--|---|
| High tech back-lit LCD display | <i>Ensures excellent visibility at all times</i> |
| Large LCD characters | <i>Ensure excellent visibility over long distances and from wide viewing angles</i> |
| Dual-colour display | <i>Provides intuitive visible feedback of value status</i> |
| Simple-to-use menu structure | <i>Gives programming continuity across all applications</i> |
| Easily configurable outputs | <i>For upper, lower and window limit settings and combinations</i> |
| Scalability | <i>Enables you to configure values to your requirements</i> |
| Dust-proof and waterproof casing (Nema4X – IP66) | <i>For top performance in all conditions</i> |
| All models conform to the latest safety standards | <i>Your world-wide partner for indicators</i> |

OMRON



COLOUR CHANGE DISPLAY

VA Process signals

The K3MA-J indicator accepts all standard process signals, including input currents (0 to 20mA; 4 to 20mA) and input voltages (from 0 to 5V; 1 to 5V; $\pm 5V$ and $\pm 10V$).

- Maximum display digits: -19999 to 99999
- Output Relay: 2SPST-NO
- Additional features: Scaling, Teaching, Forced-zero, Zero-limit functions

Immediately available:

- K3MA-J-A2 100-240 VAC
- K3MA-J-A2 24 VAC/VDC

Application areas:

- Tank pressure monitoring
- Level display
- Flow rate sensor display
- Humidity display

°C Temperature signals

The K3MA-L indicator handles multiple inputs, including two types of platinum-resistance thermometers (Pt100, JPt100) and ten types of thermocouples (K, J, T, E, L, U, N, R, S, B).

- Accuracy: $\pm 0.5\%$ of indicated value
- Maximum display digits: -1999 to 9999
- Output Relay: 1SPDT
- Features: Temperature input shift

Immediately available:

- K3MA-L-C 100-240 VAC
- K3MA-L-C 24 VAC/VDC

Application areas:

- Bearing temperature monitoring
- Plastic moulding temperature control
- Industrial furnace monitoring
- Freeze indicator

Frequency/Rate signals

The K3MA-F indicator accepts multiple inputs connected as standard voltage pulse inputs, NPN/PNP (5 kHz) or contact inputs (30 Hz).

- Sensor supply: 40mA at 12 VDC
- Maximum display digits: -19999 to 99999
- Output Relays: 2SPST-NO
- Additional features: Scaling, Teaching, Auto-zero time, Start-up time

Immediately available:

- K3MA-F-A2 100-240 VAC
- K3MA-F-A2 24 VAC/VDC

Application areas:

- Motor speed
- Axe-rotation speed
- Conveyor belt feed speed
- Low rate display

OMRON EUROPE B.V. Wegalaan 67-69, NL-2132 JD, Hoofddorp, The Netherlands. Tel: +31 (0) 23 568 13 00 Fax: +31 (0) 23 568 13 88 www.europe.omron.com

Austria
Tel: +43 (0) 1 80 19 00
www.omron.at

Belgium
Tel: +32 (0) 2 466 24 80
www.omron.be

Czech Republic
Tel: +420 267 31 12 54
www.omron.cz

Denmark
Tel: +45 43 44 00 11
www.omron.dk

Finland
Tel: +358 (0) 9 549 58 00
www.omron.fi

France
Tel: +33 (0) 1 49 74 70 00
www.omron.fr

Germany
Tel: +49 (0) 2173 680 00
www.omron.de

Hungary
Tel: +36 (0) 1 399 30 50
www.omron.hu

Italy
Tel: +39 02 32 681
www.omron.it

Netherlands
Tel: +31 (0) 23 568 11 00
www.omron.nl

Norway
Tel: +47 (0) 22 65 75 00
www.omron.no

Poland
Tel: +48 (0) 22 645 78 60
www.omron.com.pl

Portugal
Tel: +351 21 942 94 00
www.omron.pt

Russia
Tel: +7 095 745 26 64
www.russia.omron.com

Spain
Tel: +34 913 777 900
www.omron.es

Sweden
Tel: +46 (0) 8 632 35 00
www.omron.se

Switzerland
Tel: +41 (0) 41 748 13 13
www.omron.ch

Turkey
Tel: +90 (0) 216 474 00 40
www.omron.com.tr

United Kingdom
Tel: +44 (0) 870 752 08 61
www.omron.co.uk

For the Middle East, Africa and other countries in Eastern Europe, Tel: +31 (0) 23 568 13 00 www.europe.omron.com

OMRON

Although we strive for perfection, Omron Europe BV and/or its subsidiary and affiliated companies do not warrant or make any representation or guarantee of the accuracy or completeness of the information described in this document. We reserve the right to make any changes at any time without prior notice.

SF2P_K3MA_SERIES_EN_INTOL_1003