

Barebone Systems

CMI201



Medium Type for IBASE Mini-ITX Motherboards except LGA775-based

Mini-ITX Systems



>> Features:

- Mini-ITX system supports IBASE Mini-ITX motherboards
- With motherboard's I/O shields and extra two USB ports
- Available in black colors
- LEDs for Standby and Power
- One 2.5" HDD drive bay
- Optional 85W DC power supply
- Supports one PCI slot
- Supports desktop or wall mount mounting

CMI201 Specifications

System Mainboard	IBASE Mini-ITX motherboards (except LG775-based)
Construction	SECC
Chassis Color	Black
Multi-function interface board	ID721
I/O Connectors	Flexible IBASE Mini-ITX motherboard's I/O shields, COM port x3, extra USB port x2, Standby LED x1, Power LED x1, ATX power On/Off/Reset x1, DC 12V output connector x2
Expansion Slots	PCI slot x1
Storage	2.5" HDD drive bay x1
Mounting	Desktop or wall mount
Dimensions	300(W) x 72(H) x 200mm(D) (11.81" x 2.83" x 7.87")
Power Supply	Output Power: AC 60W & 85W (ATX) Input Voltage: 115~230VAC (Nom.), 5V@5A, 12V@1.5A, -12V@0.5A, +3.3V@4A, +5Vsb@0.75A

Environmental/ Mechanical:

Operating Temperature	0°C~ 45°C (32°F~113°F)
Relative Humidity	95% @ 40°C, (non-condensing)
RoHS	Available

Remarks: 1. Use only CPU/heatsink s with height fitting the chassis-not touching the chassis top cover.
2. ODM/OEM is available.

For user's manual & datasheet download, visit www.ibase.com.tw