

CMi211

Expandable Type for IBASE Mini-ITX Motherboards

Mini-ITX System



Features

- Intel® Core™2 Quad / Core™2 Duo Mobile processors
- Supports 3x RS232 & 1x RS232/422/485
- 2x 10/100/1000Base-T LAN
- 6x USB 2.0 ports
- Expansion PCI-E(x16) slot
- Supports 1x 2.5" SATA HDD drive bay

Specifications

System Mainboard	MI945P/ MI945X/ MB899X
CPU Type	Intel® Core™2 Quad Mobile Processor Intel® Core™2 Duo Mobile Processor
CPU Package	Socket P (MI945P/ MI945X) / Socket M (MB899X)
System Chipset	Intel® GM45 + ICH9M (MI945P / MI945X) Intel® 945GME + ICH7M (MB899X)
Build-In Graphic Controller	Intel® Graphics Media Accelerator X4500 (MI945P / MI945X) Intel® Graphics Media Accelerator 950 (MB899X)
Memory	800/1066MHz DDRII SDRAM up to 8GB (MI945P/ MI945X) 400/533/667MHz DDRII SDRAM up to 4GB (MB899X)
Expansion	1x PCI-E(x16) slot
Chassis Color	Black
Construction	SECC
Rear Panel External I/O	2x DB9 (serial ports) 1x DB15 (CRT) 2x RJ45 (Gigabit LAN) 4x USB 2.0 2x PS/2 (KB/MS) 1x slot for PCI/PCI-E(x16) card 1x AC-inlet Power On/Off button PWR/ HDD LED MI945P / MI945X: 6x audio jack (Line in, Line out, microphone, Side Surround, Rear Surround, Center/LFE) MB899X: 3x audio jack (Line in, Line out, microphone) 1x SPDIF
Storage	1x 2.5" HDD drive bay
Power Supply	180W Flex ATX power supply Input Voltage : 90 ~ 264 Volt Input Frequency : 47 ~ 63 Hz
Mounting	Optional wall mount kit
Dimensions	300mm(W) x 205mm(D) x 72mm(H)
Operating Temperature	0°C ~ 45°C (32°F ~ 113°F)
Storage Temperature	-20°C ~ 80°C (-4°F ~ 176°F)
Relative Humidity	5~90% @ 45°C, (non-condensing)
Vibration	Non-Operating : 1.0 grms / 5~500Hz / random Operating : 0.25 grms / 5~500Hz / random

Ordering Information

CMi211-180	Chassis for Mini-ITX, w/ 2.5" HDD bracket and 180W PSU
CMi211-250	Chassis for Mini-ITX, w/ 2.5" HDD bracket and 250W PSU

* Use only CPU/heatsink with height fitting the chassis-not touching the chassis top cover.

CMi203

Expandable Type for IBASE Mini-ITX Motherboards

Mini-ITX System



Features

- Mini-ITX system supports IBASE Mini-ITX motherboards
- Available in black color
- Supports 2x PCI slots
- With motherboard's I/O shields and extra 2x USB ports
- LEDs for Standby and Power
- One 3.5" HDD drive bay
- Optional 250W power supply
- Wall mount kit included

Specifications

System Mainboard	IBASE Mini-ITX motherboards
Chassis Color	Black
Construction	SECC
I/O Connectors	Flexible IBASE Mini-ITX motherboard's I/O shields, extra 2x USB ports, Standby LED, Power LED, ATX power On/Off/Reset, DC 12V output connectors
Rear Panel	Mini-ITX motherboard I/O shield 4x DB9 / DB15 (RS232 / VGA) PCI expansion slot AC-Inlet
Storage	1x 3.5" HDD drive bay
Power Supply	Output Power: DC 180W or 250W (ATX Power) Input Voltage: 90~264VAC full range
Mounting	Optional wall mount kit
Dimensions	345mm(W) x 225mm(D) x 100mm(H)
Operating Temperature	0°C ~ 45°C (32°F ~ 113°F)
Storage Temperature	-20°C ~ 80°C (-4°F ~ 176°F)
Relative Humidity	5~90% @ 45°C, (non-condensing)
Vibration	Non-Operating : 1.0 grms / 5~500Hz / random Operating : 0.25 grms / 5~500Hz / random

Ordering Information

CMi203-180	Chassis for Mini-ITX, w/ 180W PSU, 3.5" HDD holder, 2x PCI-E (optional IP241, IP118-R riser card & iLO LCM)
CMi203-250	Chassis for Mini-ITX, w/ 250W PSU, 3.5" HDD holder, 2x PCI-E (optional IP241, IP118-R riser card & iLO LCM)

* Use only CPU/heatsink with height fitting the chassis-not touching the chassis top cover.



01

Motherboards

02

Disk-Size SBCs

03

CPU Modules

04

PC 104 Plus

05

CPU Cards

06

RISC SBCs

07

Embedded Systems