

Barebone Systems

CM1203

Regular Type for All IBASE Mini-ITX Motherboards

Mini-ITX Systems



>> Features:

- Mini-ITX system supports IBASE Mini-ITX motherboards
- Available in black color
- Supports two PCI slots
- With motherboard's I/O shields and extra two USB ports
- LEDs for Standby and Power
- One 3.5" HDD drive bay
- Optional 250W DC power supply
- Supports desktop or wall mount mounting

CM1203 Specifications

System Mainboard	IBASE Mini-ITX motherboards
Construction	SECC
Chassis Color	Black
Multi-function interface board	ID721
I/O Connectors	Flexible IBASE Mini-ITX motherboard's I/O shields, extra USB port x2, Standby LED x1, Power LED x1, ATX power On/Off/Reset x1, 12V DC output connector x2
Expansion Slots	PCI slot x2
Storage	3.5" HDD drive bay x1
Mounting	Desktop or wall mount
Dimensions	340(W) x 100(H) x 225mm(D) (13.39" x 3.94" x 8.89")
Power Supply	Output Power: AC 180W & 250W (ATX) Input Voltage: 90~264VAC full range

Environmental/ Mechanical:

Operating Temperature	0°C ~ 45°C (32°F ~ 113°F)
Relative Humidity	95% @ 40°C, (non-condensing)
RoHS	Available

Remarks: 1. Use only CPU/heatsink s with height fitting the chassis-not touching the chassis top cover.
2. ODM/OEM is available.